



Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product identifier
- Trade name: PM Xeramic® Threadlocker Blue 20180
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- Application of the substance / the mixture Adhesives
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
- · Petromark Automotive Chemicals B.V.
- · Rooswijkweg 316
- · 1951 ME Velsen-Noord Nederland
- · Tel +31 251 211397 www.xeramic.com
- Further information obtainable from: Research & Development: sales@petromark.eu
- 1.4 Emergency telephone number: During normal business hours: Tel: +31 251 211397

SECTION 2: Hazards identification

- -2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

- Hazard pictograms Void
- Signal word Void
- Hazard statements

H412 Harmful to aquatic life with long lasting effects.

- Precautionary statements

P273 Avoid release to the environment.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- -2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- -3.2 Mixtures
- Description: Adhesive

(Contd. on page 2)

- CH-EN -

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: PM Xeramic® Threadlocker Blue

		(Contd. of page
- Dangerous components:		
CAS: 128-37-0	Butylated hydroxytoluene	≥ 0.25 - ≤ 1%
EINECS: 204-881-4	Aquatic Chronic 1, H410	
CAS: 80-15-9	α,α -dimethylbenzyl hydroperoxide	≥ 0.25 - < 1%
EINECS: 201-254-7	Org. Perox. E, H242; Acute Tox. 3, H331; STOT RE 2, H373;	
Index number: 617-002-00-8	Skin Corr. 1B, H314; Aquatic Chronic 2, H411; Acute Tox. 4,	
	H302; Acute Tox. 4, H312; STOT SE 3, H335	
	Specific concentration limits: Skin Corr. 1B; H314: C ≥ 10 %	
	Skin Irrit. 2; H315: $3 \% \le C < 10$	
	%	
	Eye Dam. 1; H318: C ≥ 3 %	
	Eye Irrit. 2; H319: $1 \% \le C < 3 \%$	
	STOT SE 3; H335: C < 10 %	
CAS: 114-83-0	2'-phenylacetohydrazide	≤ 1%
EINECS: 204-055-3	Acute Tox. 3, H301	
- Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

- -4.1 Description of first aid measures
- General information: Remove any clothing soiled by the product.
- After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: After contact with skin, wash with plenty of water.
- After eye contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

- After swallowing:

Rinse out mouth and then drink plenty of water.

If swallowed, do not induce vomiting: seek medical advice and show this container or label.

-4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- -5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- -5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide and carbon dioxide

Danger of forming toxic pyrolysis products.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- -5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

- Additional information

Cool endangered receptacles with water spray.

(Contd. on page 3)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: PM Xeramic® Threadlocker Blue

(Contd. of page 2)

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

-6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with the eyes and skin.

- 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

-6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

-6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 10 for information on "stability and reactivity".

See Section 13 for disposal information.

SECTION 7: Handling and storage

- -7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

No special precautions are necessary if used and stored according to specifications.

- -7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

- Storage class (TRGS 510, Storage of hazardous substances in non-stationary containers): 10-13
- -7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- -8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- **Appropriate engineering controls** No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

- Respiratory protection: Not required.
- Hand protection

Protective gloves on prolonged contact with skin.

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

Find below a list of appropriate protective gloves for chemical surrounding:

(Contd. on page 4)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: PM Xeramic® Threadlocker Blue

(Contd. of page 3)

Permeation time / penetration time: = 480 minutes (DIN EN 374):

Naturlatex I , Nr. 0395 oder 0403 Chloropren Nitril I, Nr. 0727

Nitril I, Nr. 0730, 0732, 0733, 0736, 0737, 0738, 0739 oder 0836

Viton, Nr. 0890 Butyl II, Nr. 0897 Butyl, Nr. 0898

Permeation time / penetration time: = 240 minutes (DIN EN 374):

Chloropren Nitril II, Nr. 0717

Nitril VI, Nr. 0754 Nitril V, Nr. 0764

of KCL company (e-mail: vertrieb@kcl.de).

of KCL company (e-mail: vertrieo@kci.de)

The recommendation is based exclusively on the chemical compatibility and the test according to EN374 under laboratory conditions.

Requirements can vary according to the use. Therefore, please always take into account the glove supplier's recommendations.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Avoid contact with the eyes.

SECTION 9: Physical and chemical properties

-9.1 Information on basic physical and chemical properties

- General Information

- Colour: Blue
- Odour: Mild

- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.

- Boiling point or initial boiling point and boiling

range Undetermined.
- Flammability Not applicable.

-Lower and upper explosion limit

- Lower: Not determined.
- Upper: Not determined.
- Flash point: > 100 °C
- Decomposition temperature: Not determined.
- pH Not determined.

- Viscosity:

- **Kinematic viscosity** Not determined.

- Dynamic at 20 °C: 1,500 mPas (Brookfield 3/20)

- Solubility

- water: Not miscible or difficult to mix.

- Partition coefficient n-octanol/water (log value)
 - Vapour pressure:
 Not determined.
 Not determined.

- Density and/or relative density

- Density at 20 °C:

- Relative density

1.12 g/cm³

Not determined.

(Contd. on page 5)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: PM Xeramic® Threadlocker Blue

	(Contd. of page
- Vapour density	Not determined.
- 9.2 Other information	
- Appearance:	
- Form:	Fluid
- Important information on protection of heal environment, and on safety.	th and
- Ignition temperature:	Product is not self-igniting.
- Explosive properties:	Product does not present an explosion hazard.
- Change in condition	Trouble does not present an expression nazara.
- Softening point/range	
- Oxidising properties	Not determined.
- Evaporation rate	Not determined.
- Information with regard to physical hazard	classes
- Explosives	Void
- Flammable gases	Void
- Aerosols	Void
- Oxidising gases	Void
- Gases under pressure	Void
- Flammable liquids	Void
- Flammable solids	Void
- Self-reactive substances and mixtures	Void
- Pyrophoric liquids	Void
- Pyrophoric solids	Void
- Self-heating substances and mixtures	Void
- Substances and mixtures, which emit flamma	
gases in contact with water	Void
- Oxidising liquids	Void
- Oxidising solids	Void
- Organic peroxides	Void
- Corrosive to metals	Void
- Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with metal-salts.
- -10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:

No dangerous products of decomposition if used and stored according to specifications.

SECTION 11: Toxicological information

- -11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

	- LD/LC50 values relevant for classification:		
Γ	80-15-9 α,α -dimethylbenzyl hydroperoxide		
r	Oral	LD50	382 mg/kg (Rat, male/female)
	Dermal	LD50	500 mg/kg (Rat, male/female)
	Inhalative	LC50/4 h	1.37 mg/l (Rat, male/female)

(Contd. on page 6)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: PM Xeramic® Threadlocker Blue

			(Contd. of page 5)
114-83-0	2'-phenyla	acetohydrazide	
Oral	LD50	270 mg/kg (Rat, male/female)	

- Skin corrosion/irritation Repeated exposure may cause skin dryness or cracking.
- Serious eye damage/irritation Slight irritant effect possible.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- Additional toxicological information:

No experimentally found toxicological data are available for this preparation.

-11.2 Information on other hazards

- Endocrine disrupting properties	
128-37-0 Butylated hydroxytoluene	List II

SECTION 12: Ecological information

- -12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- -12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects No further relevant information available.
- Remark: Harmful to fish
- Additional ecological information:
- General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or undiluted sewage system.

SECTION 13: Disposal considerations

- -13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information -14.1 UN number or ID number -ADR, IMDG, IATA Void -14.2 UN proper shipping name -ADR, IMDG, IATA Void

(Contd. on page 7)

Printing date 12.04.2023 Version number 2 (replaces version 1) Revision: 12.04.2023

Trade name: PM Xeramic® Threadlocker Blue

		(Contd. of page 6
- 14.3 Transport hazard class(es)		
- ADR, ADN, IMDG, IATA		
- Class	Void	
- 14.4 Packing group		
- ADR, IMDG, IATA	Void	
- 14.5 Environmental hazards:	Not applicable.	
- 14.6 Special precautions for user	Not applicable.	
- 14.7 Maritime transport in bulk according	ng to IMO	
instruments	Not applicable.	
- UN "Model Regulation":	Void	

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- National regulations:
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. E: Organic peroxides - Type E/F

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

 $Aquatic\ Chronic\ 2:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long-term\ aquatic\ hazard\ -\ Category\ 2$

 $A quatic\ Chronic\ 3:\ Hazardous\ to\ the\ aquatic\ environment\ -\ long-term\ aquatic\ hazard\ -\ Category\ 3$

- * Data compared to the previous version altered.